

Standard gestation stall

Gestation stalls



Description

The Standard gestation stall is the basis of any room of gestation. Simple, sturdy and with plenty of options that make it a versatile choice.

Different back door options:

Back door "double S" to facilitate insemination.

High door option allows a perfect space management and ease of use.

Self-closing back high door integrated. Convenient, easy to use and without locking parts that can be misplaced.

Materials

Smooth solid Ø20, Ø16, Ø14

Technical characteristics

- No cuts or sharp edge.
- Ease of use and assembly.
- Solid or tube frameworks in different position and number.
- Anchor legs by burying in concrete, welded plate or screw legs.
- Optional solid front door Ø16, Standard front door or Vertical front door.
- Black or galvanized finish.
- Manufacturing option solid Ø20 ext Ø14 int or Ø20 ext Ø16 int.
- Optional lengths 2m or 2,10m.
- Different widths.
- Possibility of incorporating feeding tube 70x1,5 galvanized and have it welded or independently by u-bolts and anchor.
- Consult the possibility of particular applications.



Polígono Industrial Los Arenales
C/ Camino Real 3 | 40213 | Vallelado, Segovia
(España)

Tel.: (+34) 921 150 315
Fax: (+34) 921 150 311
govi@govi.es | www.govi.es

Standard gestation stall

Gestation stalls

Image gallery

